

Wall light

OUT-01



OUT-01 is an outdoor wall light with built-in LED designed to illuminate, for instance, house facades. It can be set to shine up, down, or in both directions simultaneously. The product has built-in time functions such as astro schedule to turn on at sunset and off at sunrise automatically.

The product can be controlled wirelessly via the app or through other products from Plejd.



Light data

Luminous flux	2x300 lm
Tunable white	2,200–4,000 K
Beam angle	42°
Efficiency	85 lm/W
Dimming	0.1–100 %
RA	>90
SDCM	3
L70/B50	>60,000 h, Ta 35 °C
Light source	LED (non user replaceable)

Technical data

IP rating	IP45
Insulation class	Class I (1)
Protection	Electronic temp protection
Permissible ambient temperature	-25 to +35 °C
Battery backup	Battery life up to 10 years
Maximum power consumption	2x5 W
Energy efficiency class	F
Mains electricity	230 V~ 50 Hz
Power factor (PF)	0.9
Standby power	Pno, Psb: N/A Pnet: 0.10 W
Maximum bypass current	16 A

Radio

2.4 GHz mesh Bluetooth® <10 dBm	The Plejd mesh technology extends the range by allowing the units to communicate with each other.
---------------------------------------	---

Article list

OUT-01-W	White (RAL 9003)
OUT-01-G	Grey (RAL 7042)
OUT-01-B	Black (RAL 7021)

